


CMP 200

WALK THROUGH METAL DETECTOR











✓ Better experience with auxiliary traffic lights in the main body · Support anti-smash and automatic closing with an infrared detector, loop detector, radar detector · Arm direction can be exchanged

PARAMETERS

Gate Opening Closing Time 6s (max. 4.5m) Supply Voltage AC110V / 220V, 50 / 60Hz Power Consumption 100W (max. 120W) Remote Distance ≤ 30m Remote Frequency 430MHz Cabinet Material Cold rolled steel Boom Material Aluminum and wood Operating Temperature ≤ 90% Housing Dimensions 3s (max. 4.5m) 6s (max. 4.5m) 6un		
Supply Voltage AC110V / 220V, 50 / 60Hz Power Consumption 100W (max. 120W) Remote Distance ≤ 30m Remote Frequency 430MHz Cabinet Material Cold rolled steel Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Gate Opening	3s (max. 4.5m)
Power Consumption 100W (max. 120W) Remote Distance ≤ 30m Remote Frequency 430MHz Cabinet Material Cold rolled steel Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Closing Time	6s (max. 6m)
Remote Distance ≤ 30m Remote Frequency 430MHz Cabinet Material Cold rolled steel Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Supply Voltage	AC110V / 220V, 50 / 60Hz
Remote Frequency 430MHz Cabinet Material Cold rolled steel Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Power Consumption	100W (max. 120W)
Cabinet Material Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Remote Distance	≤ 30m
Boom Material Aluminum and wood Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Remote Frequency	430MHz
Operating Temperature -25°C ~ +75°C Operating Humidity ≤ 90%	Cabinet Material	Cold rolled steel
Operating Humidity ≤ 90%	Boom Material	Aluminum and wood
	Operating Temperature	-25°C ~ +75°C
Housing Dimensions 350 * 280 * 1010 (mm)	Operating Humidity	≤ 90%
	Housing Dimensions	350 * 280 * 1010 (mm)

WWW.BOXTELSYSTEMS.COM

CMP 200 WALK THROUGH METAL DETECTOR

PARAMETERS

Packing Dimensions	430 * 375 * 1100 (mm)
Weight	45kg
Gross Weight	47kg
Boom Type	Straight telescopic boom
Boom Weight	3.5kg(4.5m), 4.5kg(6m)
Boom Length	4.5m (packaging length 2.8m)
	6m (packaging length 3.6m)



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High Temperatures -25°C to 75°C

Software
Desktop, Web, Cloud



Access Control



Employee Self Service



Mobile App

Disclaimer: Product specifications are given here is for information purpose only and it may change at any time WITHOUT prior notice. We request our customers that before purchase, confirm with us about available features

BOXTEL SYSTEMS INTERNATIONAL PVT LTD

Website: https://www.boxtelsystems.com

Sales: sales@boxtelsystems.com **Support:** support@boxtelsystems.com