BOXTEL
DELIVERING TECHNOLOGY SOLUTIONS

FBL4000 PRO

WALK THROUGH METAL DETECTOR

Finger RFID Access Control

WALK THROUGH METAL DETECTOR

PARAMETERS

Power Requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Working Temperature	-28°C to 60°C
Working Humidity	5%RH to 80%RH
Speed of Throughput	RFID: Maximum 30/minute Fingerprint: Maximum 25/minute
Lane Width (mm)	600 (mm)
Footprint (mm*mm)	1350 * 1200
Dimension (L*W*H)	1350*300*1010 (mm)
Dimension with Packing (L*W*H)	1500*840*1100 (mm)
Weight with Packing (kg)	169kg
Net Weight (kg)	116kg
LED Indicator	Supports
Control System	SUS304 Stainless Steel

FBL4000 PRO WALK THROUGH METAL DETECTOR

PARAMETERS

Lid Material	SUS304 Stainless Steel
Barrier Material	Acrylic
Barrier Movement	Retracting
Emergency Mode	Supports
Security Level	Medium
MCBF	2 million

Software
Desktop, Web, Cloud

Access Control

Employee Self Service

Mobile App

Disclaimer : *Product specifications are given here is for information purpose only and it may change at any time WITHOUT prior notice. We request our customers that before purchase, confirm with us about available features*