MTS1000 SERIES

WALK THROUGH METAL DETECTOR

Finger	RFID	Access Control

WALK THROUGH METAL DETECTOR

PARAMETERS

Power Requirements	AC110V/220V, 50/60Hz
Power Consumption	Running: 40W Standby: 10W
Working Temperature	-28°C to 60°C
Working Humidity	5%RH to 80%RH
Speed of Throughput	RFID: Maximum 25/minute Fingerprint: Maximum 20/minute
Lane Width (mm)	478 (mm)
Arm Length	478 (mm)
Footprint (mm*mm)	250 * 138 (mm)
Dimension (L*W*H)	798 * 750 * 950 (mm)
Dimension with Packing (L*W*H)	380 * 450 * 1150 (mm)
Gross Weight	40 kg
Net Weight (kg)	35 kg
LED Indicator	Yes
Control System	Input controlled by dry conta

MST1000 SERIES WALK THROUGH METAL DETECTOR

PARAMETERS

Cabinet Material	SUS304 (optional SUS316)
Lid Material	Acrylic
Barrier Material	SUS304
Barrier Movement	Rotated
Emergency Mode	Support (power off drop arm)
Security Level	Medium
Options / Accessories	Cardbox, Remote control, QR
Certification	CE and FCC

Accepts moist and rough Finger

Accepts Color & Mahendi Finger

Compact & lightweight design

Unaffected by High Temperatures 0° ~ 50°

Software

Desktop, Web, Cloud

Access Control

Employee Self Service

Mobile App